

HOTEMP SUPER M 121 S

High-temperature oil for the lubrication of roller bar chains



Your benefits at a glance

- Maximum machine life even at high operating temperatures due to good lubricity, spreading and wetting properties
- Reduced oil consumption and fume formation due to low evaporation losses at high temperatures
- Regenerates and dissolves pasty oil residues, hence less maintenance and unobstructed lubricating systems

Your requirements - our solution

HOTEMP SUPER M 121 S is a low-viscous, solvent-free and thermally stable ester oil.

Application

HOTEMP SUPER M 121 S is recommended and used for the lubrication of roller bar chains in Conti-Roll presses of Messrs. Siempelkamp.

Application notes

HOTEMP SUPER M 121 S is an advanced product version based on HOTEMP SUPER C 2-50. With regard to the longer chain pins supporting the roller bars of Siempelkamp Conti presses (as of 1999 year of construction), the penetrating properties have been considerably improved. Thereby, wetting is ensured over the entire

pin length. HOTEMP SUPER M 121 S is used in a separate lubrication circuit to lubricate the roller bar chains.

HOTEMP SUPER M 121 S can also be used for chain lubrication wherever a low-viscous oil is required, as well as for cleaning purposes.

HOTEMP SUPER M 121 S dissolves and regenerates pasty oil residues.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.

Pack sizes	HOTEMP SUPER M 121 S
Drum 200 l	+

Characteristics	HOTEMP SUPER M 121 S
Article number	002122
Composition, type of oil	ester oil
Appearance	clear
Colour space	yellow
Service temperature, lower limit	0 °C
Service temperature, upper limit	250 °C
Density, DIN 51757, 20°C	approx. 0.97 g/cm ³
Flash point, DIN EN ISO 2592, Cleveland open cup	≥ 270 °C
Kinematic viscosity, DIN EN ISO 3104 / DIN 51562-1 / ASTM D445 / ASTM D7042, 100°C	approx. 8.2 mm ² /s

HOTEMP SUPER M 121 S

High-temperature oil for the lubrication of roller bar chains



Characteristics	HOTEMP SUPER M 121 S
Kinematic viscosity, DIN EN ISO 3104 / DIN 51562-1 / ASTM D445 / ASTM D7042, 40°C	approx. 55 mm ² /s
Copper corrosion, DIN EN ISO 2160, 24 h, 160°C	1 - 160 - 24 corrosion degree
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx. 60 months	

Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 90 years.

Klüber Lubrication München GmbH & Co. KG /
Geisenhausenerstraße 7 / 81379 München / Germany /
phone +49 89 7876-0 / fax +49 89 7876-333.

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München GmbH & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München GmbH & Co. KG and if source is indicated and voucher copy is forwarded.