

# POLYLUB GA 352 P

Adhesive long-term grease with good water resistance



## Your benefits at a glance

- Good water resistance
- Good adhesion

## Your requirements - our solution

POLYLUB GA 352 P is an aluminium complex thickened grease incorporating a semi synthetic base oil.

### Application

POLYLUB GA 352 P is used for the lubrication of rolling and plain bearings, racks, cylinder guides, pneumatic cylinders, load rollers and slideways.

POLYLUB GA 352 P is suitable for machines and installations in the food-processing and related industries where contact with the food product is excluded.

## Application notes

POLYLUB GA 352 P can be applied by means of brush, spatula or grease gun.

## Material safety data sheets

Material safety data sheets can be requested via our website [www.klueber.com](http://www.klueber.com). You may also obtain them through your contact person at Klüber Lubrication.

Pack sizes	POLYLUB GA 352 P
Cartridge 400 g	+
Can 1 kg	+
Bucket 25 kg	+
Drum 180 kg	+

Characteristics	POLYLUB GA 352 P
Article number	097095
Composition, thickener	aluminium complex soap
Composition, type of oil	mineral oil , synthetic hydrocarbon oil
Appearance	transparent
Colour space	yellow
Texture	fibrous , homogeneous
Service temperature, lower limit	-35 °C
Service temperature, upper limit, in case of continuous lubrication	120 °C
Worked penetration, DIN ISO 2137 / ASTM D217, 25°C, lower limit	280 0.1 mm

# POLYLUB GA 352 P

Adhesive long-term grease with good water resistance



Characteristics	POLYLUB GA 352 P
Worked penetration, DIN ISO 2137 / ASTM D217, 25°C, upper limit	310 0.1 mm
Shear viscosity, Klüber method: PN 008@DIN 53019-1, equipment: rotational viscometer, 25°C, 300 s <sup>-1</sup> , lower limit	3000 mPas
Shear viscosity, Klüber method: PN 008@DIN 53019-1, equipment: rotational viscometer, 25°C, 300 s <sup>-1</sup> , upper limit	5500 mPas
SKF-EMCOR, DIN 51802, Klüber method: distilled water, 168 h	≤ 1 corrosion degree
Dropping point, DIN ISO 2176 / IP 396	≥ 220 °C
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	24 months

## Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 90 years.

Klüber Lubrication München GmbH & Co. KG /  
Geisenhausenerstraße 7 / 81379 München / Germany /  
phone +49 89 7876-0 / fax +49 89 7876-333.

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München GmbH & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München GmbH & Co. KG and if source is indicated and voucher copy is forwarded.