

Klübersynth HM 2-220

High-temperature oil for the glass industry



Your benefits at a glance

- Lower oil costs due to lower consumption
- Lower waste water disposal costs due to excellent water separation ability
- Much less machine contamination, hence lower cleaning costs
- Smooth machine operation due to good pumpability and precise metering by centralised lubricating systems
- Higher machine efficiency due to uninterrupted operation with higher output
- Higher machine reliability due to less residue formation
- Less machine wear also at high temperatures
- No starting-up problems, restart of cooled-down machine 20% to 30% faster thanks to good temperature-viscosity behaviour
- Changeover to Klübersynth HM 2-220 easy as miscible with mineral oil

Your requirements - our solution

Klübersynth HM 2-220 is a synthetic high-temperature oil especially developed for the glass industry. Besides the normal temperature range, Klübersynth HM 2-220 is especially suitable for the high-temperature range because its evaporation loss at elevated temperatures is very low. The product has good penetration properties and forms a lubricant film very quickly. Klübersynth HM 2-220 is free from solids, which helps to avoid sedimentation.

Application

Klübersynth HM 2-220 is suitable for all IS machines. It can be used for all friction points in the normal and high-temperature sections which are lubricated through a centralized lubrication system. In addition, Klübersynth HM 2-220 is suitable for conveyor and cross

belt chains which are lubricated by means of oil spray systems, drip oilers, centralized lubrication system, or by hand (oil feeder/brush).

Application notes

Keeping the friction point always covered with Klübersynth HM 2-220 ensures good wear protection and prevents impeded operation and residues. To achieve optimum efficiency it is important not to mix Klübersynth HM 2-220 with other oils.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.

Pack sizes	Klübersynth HM 2-220
Canister 20 l	+
Drum 200 l	+
Container 1000 l	+

Characteristics	Klübersynth HM 2-220
Article number	002115
Composition, type of oil	ester oil , synthetic hydrocarbon oil

Klübersynth HM 2-220

High-temperature oil for the glass industry



Characteristics	Klübersynth HM 2-220
Appearance	clear
Colour space	yellow
Service temperature, upper limit	250 °C
Density, DIN 51757, 20°C	approx. 0.92 g/cm ³
Kinematic viscosity, DIN EN ISO 3104 / DIN 51562-1 / ASTM D445 / ASTM D7042, 100°C	approx. 25 mm ² /s
Kinematic viscosity, DIN EN ISO 3104 / DIN 51562-1 / ASTM D445 / ASTM D7042, 40°C	approx. 220 mm ² /s
Four-ball tester, welding load, DIN 51350-2	≥ 2200 N
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months

Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 90 years.

Klüber Lubrication München GmbH & Co. KG /
Geisenhausenerstraße 7 / 81379 München / Germany /
phone +49 89 7876-0 / fax +49 89 7876-333.

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München GmbH & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München GmbH & Co. KG and if source is indicated and voucher copy is forwarded.