

Klübersynth RA 44-702, -1502, -3500, -3502

for noise reduction and mechanical damping



Your benefits at a glance

- Soft feel effect (haptics)
- Noise reduction
- Good compatibility with plastics
- Low oil separation

Your requirements - our solution

Klübersynth RA 44-702, RA 44-1502, RA 44-3500 and RA 44-3502 are fully synthetic special greases of high viscosity providing haptic and acoustic damping to your components for a better touch-feel. This enables you to provide mechanical damping to slow-moving components and hence reduce noises, e.g. inside cars.

Application

Klübersynth RA 44-702, RA 44-1502, RA 44-3500 and RA 44-3502 are preferably used for plastic/plastic and plastic/metal material pairings. These products enable you to set defined shifting forces and compensate for tolerances. All products of the Klübersynth RA series have a wide service temperature range from -40 °C to 130 °C (Klübersynth RA 44-702 even offers down to -50 °C). When applied to enclosed systems such as car seat backrest fittings, short-term peaks of up to 180 °C can be tolerated, e.g. in drying ovens.

Applications in motor cars:

mechanical switches and rotary controls, ventilation flaps, sun visors, ashtrays, cup holders, storage boxes, window lifter guide rails, armrest and seat adjustment mechanisms (vertical and horizontal), sunroofs, etc.

Further applications:

precision engineering and optical instruments, fasteners, household appliances and white goods, office machinery and computers, pneumatics and O-rings, sports equipment.

Compatibility with elastomers:

Klübersynth RA 44-702, RA 44-3500 and RA 44-3502 were especially developed for the lubrication of plastic parts inside cars. For this reason, comprehensive tests were performed according to DIN EN ISO 22088 (stress cracking). The results show that these greases are neutral to most plastic materials. Owing to the many different plastic compositions, we recommend checking the material's compatibility with the grease prior to series application.

Application notes

These products can be applied by means of grease gun, brush or spatula as well as via automatic lubricating systems. Klübersynth RA 44-702 and RA 44-3502 contain a UV indicator for easy quality inspection of minimum quantity lubrication. The UV check can be made with a wavelength of 366 nm.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.

Pack sizes	Klübersynth RA 44-702	Klübersynth RA 44-1502	Klübersynth RA 44-3500	Klübersynth RA 44-3502
Can 1 kg	+	+	+	+
Bucket 25 kg	+	+	+	+
Bucket 50 kg	+			
Drum 170 kg	+	+	+	+

Klübersynth RA 44-702, -1502, -3500, -3502

for noise reduction and mechanical damping



Characteristics	Klübersynth RA 44-702	Klübersynth RA 44-1502	Klübersynth RA 44-3500	Klübersynth RA 44-3502
Article number	012264	012263	012311	012262
Composition, thickener	lithium soap	lithium soap	lithium soap	lithium soap
Composition, type of oil	synthetic hydrocarbon oil	synthetic hydrocarbon oil	synthetic hydrocarbon oil	synthetic hydrocarbon oil
Colour space	beige	beige	beige	beige
Service temperature, lower limit	-50 °C	-40 °C	-40 °C	-40 °C
Service temperature, upper limit	130 °C	130 °C	130 °C	130 °C
Density, Klüber method: PN 024, 20°C	approx. 0.87 g/cm ³	approx. 0.87 g/cm ³	approx. 0.85 g/cm ³	approx. 0.87 g/cm ³
Worked penetration, DIN ISO 2137 / ASTM D217, 25°C, lower limit	265 0.1 mm	285 0.1 mm	340 0.1 mm	275 0.1 mm
Worked penetration, DIN ISO 2137 / ASTM D217, 25°C, upper limit	295 0.1 mm	315 0.1 mm	370 0.1 mm	305 0.1 mm
Shear viscosity, Klüber method: PN 008@DIN 53019-1, equipment: rotational viscometer, 25°C, 300 s ⁻¹ , lower limit	6000 mPas	8000 mPas	12000 mPas	16000 mPas
Shear viscosity, Klüber method: PN 008@DIN 53019-1, equipment: rotational viscometer, 25°C, 300 s ⁻¹ , upper limit	12000 mPas	15000 mPas	18000 mPas	23000 mPas
Kinematic viscosity of the base oil, DIN EN ISO 3104 / DIN 51562-1 / ASTM D445 / ASTM D7042, 40°C	approx. 720 mm ² /s	approx. 1500 mm ² /s	approx. 3500 mm ² /s	approx. 3500 mm ² /s
SKF-EMCOR, DIN 51802, Klüber method: distilled water, 168 h	≤ 1 corrosion degree	≤ 1 corrosion degree		≤ 1 corrosion degree
Oil separation, DIN 51817 N, 168 h, 40°C	≤ 3 % by weight	≤ 3 % by weight	≤ 5 % by weight	≤ 3 % by weight
Flow pressure, DIN 51805-2, -40°C		≤ 1400 mbar	≤ 1400 mbar	≤ 1400 mbar
Flow pressure, DIN 51805-2, -50°C	≤ 1400 mbar			
Low temperature torque, IP 186, -40°C, running torque	approx. 140 mNm			approx. 290 mNm
Low temperature torque, IP 186, -40°C, starting torque	approx. 150 mNm			approx. 510 mNm
Dropping point, DIN ISO 2176 / IP 396	≥ 180 °C	≥ 180 °C	≥ 180 °C	≥ 180 °C
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months	24 months	24 months	36 months

Klübersynth RA 44-702, -1502, -3500, -3502

for noise reduction and mechanical damping



Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 90 years.

Klüber Lubrication München GmbH & Co. KG /
Geisenhausenerstraße 7 / 81379 München / Germany /
phone +49 89 7876-0 / fax +49 89 7876-333.

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München GmbH & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München GmbH & Co. KG and if source is indicated and voucher copy is forwarded.